

Apple Pay via CyberSource

Use the values in the tables below to configure for using **Apple Pay** via the **CyberSource** payment provider/authorizer with the described settings.

(The procedures for accessing and configuring these settings are described in [Add an Authorizer](#).)

Parameter	Value	Comments
AUTHORIZER NAME	CyberSource	Can be any meaningful value.
AUTHORIZER CODE	CyberSource	This value should exactly match the provider/authorizer Bean implementation. (Service Implementation Bean is a term used in Java Platform, Enterprise Edition, for a Java object implementing a Web service.) Do not change if you are not sure.
SITE URL Test: Production:	https://ics2wstesta.ic3.com/commerce/1.x/transactionProcessor/CyberSourceTransaction_NVP_1.138.wsdl https://ics2wsa.ic3.com/commerce/1.x/transactionProcessor/CyberSourceTransaction_NVP_1.138.wsdl	The field must be populated, but the value is not currently used. Any value is valid. Suggest using specified values for consistency/clarity.
LOGIN URL Test: Production:	https://ics2wstesta.ic3.com/commerce/1.x/transactionProcessor https://ics2wsa.ic3.com/commerce/1.x/transactionProcessor	URL/SOAP Endpoint for payment processing.
CUSTOM URL 1		Not used
START DATE	12/20/18	Effective date
END DATE		Ending date, as applicable. Can be empty.
STATUS	Active	Should be "Active" for the current provider. (Status of "New" is not recommended)