

CancelBackorder

Description

This message is created and sent as an outbound message when a back order is cancelled in EDGE.

Request

URL	URL from associated message destination pipe				
Parameters	Name	Type	Required	Description	Index
	requestId	String	Y	Unique message identifier	
	sourceSystemId	String	Y	EDGE Merchant identifier (MessageDestination.xRefMerchantId)	
	destinationSystemId	String	Y	System initiating message (MessageDestination.providerCode)	
	messageName	String	Y	Fixed value "CancelBackorder" will be sent	
	orderHeaderId	Number	Y	Order identifier	Y
	cancelDate	String	Y	Cancellation date in ISO 8601 format	
	clientReference	String	N	Order client reference	Y
	items	Object Array	Y	Array of objects containing cancelled items	
	• quantity	Number	Y	Cancelled quantity	
	• sku	String	Y	SKU associated with catalog item	
	• originalQuantity	Number	Y	Original quantity	

Example**JSON**

```
{
  "orderHeaderId": 50003391,
  "cancelDate": "2021-03-31",
  "clientReference": "autoship_118",
  "items": [
    {
      "sku": "Abyss106",
      "quantity": 3,
      "originalQuantity": 3
    }
  ],
  "requestId": "101696",
  "sourceSystemId": "OMSJaggedPeakMerchant",
  "destinationSystemId": "WMSTestProvider",
  "messageName": "CancelBackorder"
}
```

XML

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<CancelBackorderRequest>
  <RequestId>101696</RequestId>
  <SourceSystemId>OMSJaggedPeakMerchant</SourceSystemId>
  <DestinationSystemId>WMSTestProvider</DestinationSystemId>
  <MessageName>CancelBackorder</MessageName>
  <OrderHeaderId>50003391</OrderHeaderId>
  <CancelDate>2021-03-31</CancelDate>
  <ClientReference>autoship_118</ClientReference>
  <Items>
    <Item>
      <SKU>Abyss106</SKU>
      <Quantity>3</Quantity>
      <OriginalQuantity>3</OriginalQuantity>
    </Item>
  </Items>
</CancelBackorderRequest>
```

Response

Parameters	Name	Type	Description
	resultCode	String	OK or FAIL
	resultMessage	String	Error description if an request failed
Example	<div style="border: 1px solid black; padding: 5px;"> <p>Success</p> <pre>{ "resultCode": "OK", "resultMessage": "" }</pre> </div>		

Example**Failure**

```
{  
  "resultCode": "FAIL",  
  "resultMessage": "Error message here."  
}
```